

(6) Y6-30-12 型锅炉离心引风机

主要用于小型锅炉和快装锅炉的引风系统，条件性能相近者亦可选用。性能如下

机 号	传 动 方 式	转 速 r/min	序 号	全 压 Pa	流 量 m ³ /h	内效率 %	电 动 机		配用锅炉 t/h	
							型 号	功 率 kW		
3.5	C	2350	1	853	655	66.0	Y801-2B ₁	0.75	0.2	
			2	843	745	68.0				
			3	834	834	70.0				
			4	824	923	72.0				
			5	800	1000	72.0				
			6	765	1103	66.0				
			7	727	1192	63.0				
4.3	C	2260	1	1206	1169	66.0	Y90S-2B ₁	1.5	0.2	
			2	1187	1328	68.0				
			3	1176	1487	70.5				
			4	1170	1700	71.0				
			5	1108	1806	70.0				
			6	1078	1966	67.0				
			7	1020	2125	64.0				
4.8	C	2250	1	1490	1619	66.0	Y90L-2B ₁	2.2	0.5	
			2	1470	1840	68.0				
			3	1450	2060	70.5				
			4	1420	2300	72.0				
			5	1392	2502	71.0				
			6	1333	2723	68.0				
			7	1265	2944	65.0				
5.4	C	2300	1	2157	2202	66.0	Y100L-2B ₁	3	0.5	
			2	2128	2503	68.0				
			3	2098	2804	70.5				
			4	2060	3100	73.0				
			5	1981	3405	70.0				
			6	1922	3705	68.0				
			7	1833	3963	66.0				
6.5	C	2150	1	2383	2926	77.0	Y112M-2B ₁	4	1	
			2	2433	3325	79.0				
			3	2328	3725	80.0				
			4	2288	4000	81.5	Y132S ₁ -2B ₁	5.5		
			5	2206	4263	81.0				
			6	2137	4604	80.0				
			7	2020	4945	77.5				
7.5	C	1900	1	2598	5216	77.5	Y132M-4B ₁	7.5	2	
			2	2559	5926	80.0				
			3	2530	6622	81.0				
			4	2500	6600	81.5				
			5	2392	7349	81.2				
			6	2324	8060	80.0	Y160M-4B ₁	11		
			7	2196	8771	77.5				
		1800	1	2736	5000	78.0	Y132M-4B ₁	7.5	2	
			2	2726	5500	81.0				
			3	2716	5900	82.0				
			4	2598	6200	82.0				
			5	2530	6500	80.0				
			6	2500	7000	78.0	Y160M-4B ₁	11		
			7	2432	7800	76.0				
8.6	C	1850	1	3226	9494	78.0	Y180M-4B ₁	18.5	4	
			2	3187	10789	80.0				
			3	3138	12083	81.3				
			4	3098	13778	82.0				
			5	3040	14000	81.5				
			6	2883	15967	80.0	Y180L-4B ₁	22		
			7	2736	17262	77.5				