

转 速 r/min	序 号	流 量 m ³ /h	全 压 Pa	内效率 %	内功率 kW	所需 功率 kW	电 动 机		三 角 带		主轴皮带轮 代 号	电机皮带轮 代 号	电机导轨部 代 号 (2套)	
							型 号	功率 kW	型 号	根 数 内周长 (mm)				
630	1	30362	863	86.7	8.37	10.13	Y180L-6	15	C	2	3550	75-C2-480	48-C2-310	3912-014
	2	33054	852	88.7	8.79	10.64								
	3	35745	818	89	9.10	11.02								
	4	38050	778	88.2	9.30	11.26								
	5	40290	735	86.6	9.47	11.46								
	6	42498	684	84.2	9.56	11.58								
560	1	26989	682	86.7	5.88	7.11	Y160M-6	7.5	C	2	3550	75-C2-480	42-C2-280	3912-014
	2	29381	673	88.7	6.17	7.47								
	3	31774	646	89	6.39	7.74	Y160L-6	11						
	4	33822	615	88.2	6.53	7.91								
	5	35813	580	86.6	6.65	8.05								
	6	37776	540	84.2	6.72	8.13								
500	1	24097	543	86.7	4.18	5.28	Y160M-6	7.5	C	2	3550	75-C2-480	55-C2-250	3912-014
	2	26233	536	88.7	4.39	5.55								
	3	28369	515	89	4.55	5.75								
	4	30198	490	88.2	4.65	5.87								
	5	31976	462	86.6	4.73	5.98								
	6	33728	430	84.2	4.78	5.79								
450	1	21687	440	86.7	3.05	3.85	Y132M1-6	4	C	2	3550	75-C2-480	38-C2-225	3912-013
	2	23610	434	88.7	3.20	4.05								
	3	25532	417	89	3.32	4.19	Y132M2-6	5.5						
	4	27178	397	88.2	3.39	4.28								
	5	28778	374	86.6	3.45	4.36								
	6	30356	348	84.2	3.49	4.40								
400	1	19278	347	86.7	2.14	2.71	Y132S-6	3	C	2	3150	75-C2-480	38-C2-200	3912-013
	2	20986	343	88.7	2.25	2.84								
	3	22695	329	89	2.33	2.94								
	4	24158	313	88.2	2.38	3.01								
	5	25581	296	86.6	2.42	3.06								
	6	26983	275	84.2	2.45	3.09								

转 速 r/min	序 号	流 量 m ³ /h	全 压 Pa	内效率 %	内功率 kW	所需 功率 kW	电 动 机		三 角 带		主轴皮带轮 代 号	电机皮带轮 代 号	电机导轨部 代 号 (2套)	
							型 号	功率 kW	型 号	根 数				内周长 (mm)
900	1	102810	3157	86.7	102.81	124.45	Y315L2 -6	132	E	6	5600	150-E6-640	80-E6-600	3912-020
	2	111930	3115	88.7	107.98	130.70								
	3	121040	2990	89	111.80	135.33								
	4	128840	2844	88.2	114.28	138.33	Y315M -6	160						
	5	136430	2684	86.6	116.35	140.84								
	6	143910	2497	84.2	117.48	142.20								
800	1	91392	2489	86.7	72.21	87.41	Y315L1 -6	110	D	6	5600	150-D6-640	80-D6-530	3912-020
	2	99493	2456	88.7	75.84	91.81								
	3	107590	2357	89	78.53	95.06								
	4	114530	2242	88.2	80.27	97.16								
	5	121270	2117	86.6	81.72	98.92								
	6	127920	1969	84.2	82.52	99.89								
710	1	81110	1957	86.7	50.48	61.10	Y315S -6	75	C	7	5600	150-C7-640	80-C7-470	3912-020
	2	88300	1931	88.7	53.02	64.18								
	3	95490	1853	89	54.89	66.45								
	4	101640	1763	88.2	56.11	67.92								
	5	107630	1664	86.6	57.12	69.15								
	6	113520	1549	84.2	57.68	69.83								
630	1	71971	1538	86.7	35.27	42.69	Y280M -6	55	C	6	5600	150-C6-640	75-C6-420	3912-017
	2	78351	1518	88.7	37.04	44.84								
	3	84730	1457	89	38.35	46.42								
	4	90193	1386	88.2	39.2	47.45								
	5	95503	1309	86.6	39.91	48.31								
	6	100730	1218	84.2	40.30	48.78								
560	1	63974	1214	86.7	24.77	29.98	Y250M -6	37	C	5	4500	150-C5-640	65-C5-375	3912-017
	2	69645	1198	88.7	26.01	31.49								
	3	75316	1150	89	26.93	32.60								
	4	80172	1094	88.2	27.53	33.33								
	5	84892	1033	86.6	28.03	33.93								
	6	89544	961	84.2	28.30	34.26								

转 速 r/min	序 号	流 量 m ³ /h	全 压 Pa	内效率 %	内功率 kW	所需 功率 kW	电 动 机		三 角 带		主轴皮带轮 代 号	电机皮带轮 代 号	电机导轨带 代 号 (2 套)	
							型 号	功率 kW	型 号	根 数				内周长 (mm)
500	1	57120	967	86.7	17.63	21.34	Y225M-6	30	B	6	4500	150-B6-640	60-B6-355	3912-015
	2	62183	954	88.7	18.52	22.41								
	3	67246	916	89	19.17	23.21								
	4	71582	872	88.2	19.60	23.72								
	5	75796	823	86.6	19.95	24.15								
	6	79950	766	84.2	20.15	24.39								
450	1	51408	783	86.7	12.85	15.56	Y200L1-6	18.5	B	5	4000	150-B5-640	55-B5-300	3912-015
	2	55965	773	88.7	13.50	16.34								
	3	60521	742	89	13.98	16.92								
	4	64423	706	88.2	14.29	17.29								
	5	68216	666	86.6	14.54	17.61								
	6	71955	620	84.2	14.69	17.78								
400	1	45696	618	86.7	9.03	10.93	Y180L-6	15	B	4	4000	150-B4-640	48-B5-270	3912-014
	2	49746	610	88.7	9.48	11.48								
	3	53797	586	89	9.82	11.88								
	4	57265	557	88.2	10.03	12.15								
	5	60637	526	86.6	10.21	12.36								
	6	63960	490	84.2	10.31	12.48								
355	1	40553	487	86.7	6.31	7.64	Y160L-6	11	B	3	4000	150-B3-640	42-B3-240	3912-014
	2	44150	480	88.7	6.63	8.02								
	3	47745	461	89	6.86	8.31								
	4	50823	439	88.2	7.01	8.49								
	5	53815	414	86.6	7.14	8.64								
	6	56764	386	84.2	7.21	8.73								
315	1	35985	383	86.7	4.41	5.57	Y160M-6	7.5	B	3	4000	150-B3-640	42-B3-210	3912-014
	2	39175	378	88.7	4.63	5.85								
	3	42365	363	89	4.79	5.80								
	4	45096	345	88.2	4.90	5.93								
	5	47751	326	86.6	4.99	6.04								
	6	50368	303	84.2	5.04	6.10								

转 速	序 号	流 量 m ³ /h	全 压 Pa	内效率 %	内功率 kW	所需 功率 kW	电 动 机 型 号	功 率 kW	三 角 带 型 号	根 数	内周长 (mm)	主轴皮带轮 代 号	电机皮带轮 代 号	电机号铭部 代 号 (2套)
710	1	158410	3069	86.7	154.04	186.46	Y355-8	220	E	7	7100	150-E7-800	100-E7-790	3912-020
	2	172460	3029	88.7	161.79	195.84								
	3	186500	2907	89.	167.51	202.76								
	4	198520	2765	88.2	171.23	207.27								
	5	210210	2609	86.6	174.33	211.02								
	6	221730	2427	84.2	176.03	213.08								
630	1	140560	2411	86.7	107.62	130.27	Y355-8	160	E	6	7100	150-E6-800	100-E6-690	3912-020
	2	153020	2379	88.7	113.03	136.81								
	3	165480	2284	89	117.03	141.65								
	4	176150	2172	88.2	119.62	144.79								
	5	186530	2050	86.6	121.79	147.43								
	6	196750	1908	84.2	122.98	148.86								
560	1	124950	1902	86.7	75.59	91.50	Y315L2-8	110	D	6	6300	150-D6-800	80-D6-610	3912-020
	2	136020	1877	88.7	79.39	96.10								
	3	147100	1801	89	82.20	99.50								
	4	156580	1714	88.2	84.02	101.70								
	5	165800	1618	86.6	85.54	103.54								
	6	174890	1505	84.2	86.37	104.55								
500	1	111560	1514	86.7	53.80	65.13	Y315M-8	75	D	4	6300	150-D4-800	80-D4-550	3912-020
	2	121450	1494	88.7	56.51	68.40								
	3	131340	1434	89.	58.51	70.82								
	4	139800	1364	88.2	59.80	72.39								
	5	148040	1288	86.6	60.89	73.70								
	6	156150	1199	84.2	61.48	74.42								
450	1	100400	1225	86.7	39.22	47.48	Y315S-8	55	C	6		150-C6-500	80-C6-500	3912-020
	2	109300	1209	88.7	41.19	49.86								
	3	118200	1161	89	42.65	51.63				7		150-C7-500	80-C7-500	
	4	125820	1104	88.2	43.60	52.77								
	5	133230	1042	86.6	44.39	53.73								
	6	140530	970	84.2	44.82	54.25								

4-72 No. 20B 离心通风机性能与选用件表

转 速 r/min	序 号	流 量 m³/h	全 压 Pa	内效率 %	内功率 kW	所需 功率 kW	电 动 机		三 角 带		主轴皮带轮 代 号	电机皮带轮 代 号	电机导轨部 代 号 (2套)	
							型 号	功率 kW	型 号	根 数				内周长 (mm)
400	1	89250	967	86.7	27.55	33.34	Y280S-8	37	C	5	5600	150-C5-800	75-C5-440	3912-017
	2	97161	954	88.7	28.93	35.02								
	3	105070	916	89	29.96	36.26								
	4	111840	872	88.2	30.62	37.06								
	5	118430	823	86.6	31.17	37.73								
	6	124920	766	84.2	31.48	38.10								
355	1	79209	761	86.7	19.26	23.31	Y250M-8	30	B	7	5600	150-B7-800	65-B7-390	3912-017
	2	86230	751	88.7	20.22	24.48								
	3	93252	721	89	20.94	25.35								
	4	99264	686	88.2	21.40	25.91								
	5	105100	648	86.6	21.79	26.38								
	6	110860	603	84.2	22.00	26.64								
315	1	70284	599	86.7	13.45	16.28	Y225M-8	22	B	5	5600	150-B5-800	60-B5-345	3912-015
	2	76514	591	88.7	14.13	17.10						150-B6-800	60-B6-345	
	3	82744	568	89	14.63	17.71								
	4	88079	540	88.2	14.95	18.10								
	5	93265	510	86.6	15.22	18.43								
	6	98376	475	84.2	15.37	18.61								
280	1	62475	473	86.7	9.45	11.44	Y200L-8	15	B	4	5600	150-B4-800	55-B4-310	3912-015
	2	68013	467	88.7	9.92	12.01						150-B5-800	55-B5-310	
	3	73551	448	89	10.27	12.44								
	4	78293	426	88.2	10.50	12.71								
	5	82902	403	86.6	10.69	12.94								
	6	87445	375	84.2	10.80	13.07								
250	1	55781	377	86.7	6.73	8.14	Y180L-8	11	B	4	5600	150-B4-800	48-B4-275	3912-014
	2	60726	372	88.7	7.06	8.55								
	3	65670	357	89	7.31	8.85								
	4	69904	340	88.2	7.48	9.05								
	5	74020	321	86.6	7.61	9.21								
	6	78076	299	84.2	7.68	9.30								

(3) 4-72 型 离 心 通 风 机

用于般工厂及大型建筑物的室内通风换气或输送空气及其它不自燃、不易爆、不挥发、对人体无害、对钢材无腐蚀性之气体；
B4-72 型离心通风机可排送易燃、易挥发性气体；F4-72 型离心通风机主要用于输送腐蚀性气体。性能如下

机 号	传 动 方式	转 速 r/min	序 号	流 量 m³/h	全 压 Pa	内效率 %	内功率 kW	所 需 功率 kW	电 动 机		地脚螺栓 GB799-76 (4个)	螺 母 GB6170-86 (4个)	垫 圈 GB96-85 (4个)
									型 号	功率 kW			
2.8	A	2900	1	1131	994	69.3	0.45	0.67	Y90S-2 (B35)	1.5	M8×220	M8	8
			2	1310	966	73.2	0.48	0.72					
			3	1480	933	75.5	0.51	0.71					
			4	1659	887	76.8	0.53	0.74					
			5	1828	835	76.9	0.55	0.77					
			6	2007	770	73.6	0.57	0.79					
			7	2177	702	73.2	0.58	0.81					
			8	2356	606	69.3	0.57	0.80					
3.2	A	2900	1	1688	1300	69.3	0.88	1.23	Y90L-2 (B35)	2.2	M8×220	M8	8
			2	1955	1263	73.2	0.93	1.31					
			3	2209	1220	75.5	0.99	1.38					
			4	2476	1160	76.8	1.03	1.34					
			5	2729	1091	76.9	1.07	1.39					
			6	2996	1006	73.6	1.10	1.43					
			7	3250	918	73.2	1.13	1.47					
			8	3517	792	69.3	1.11	1.45					
3.2	A	1450	1	844	324	69.3	0.11	0.16	Y90S-4 (B35)	1.1	M8×220	M8	8
			2	978	315	73.2	0.12	0.17					
			3	1104	304	75.5	0.12	0.19					
			4	1238	289	76.8	0.13	0.19					
			5	1365	272	76.9	0.13	0.20					
			6	1498	251	73.6	0.14	0.21					
			7	1625	229	73.2	0.14	0.21					
			8	1758	198	69.3	0.14	0.21					
3.6	A	2900	1	2664	1578	74.2	1.56	2.03	Y100L-2 (B35)	3	M10×220	M10	10
			2	3045	1531	77.8	1.65	2.15					
			3	3405	1481	80.3	1.73	2.25					
			4	3786	1419	82.1	1.81	2.35					
			5	4146	1343	82.6	1.86	2.42					
			6	4527	1256	81.8	1.92	2.50					
			7	4887	1144	79.5	1.95	2.53					
			8	5268	989	74.3	1.94	2.52					

4-72 № 3. 6A、4A、4. 5A 离心通风机性能与选用件表

机号	传动方式	转速 r/min	序号	流量 m³/h	全压 Pa	内效率 %	内功率 kW	所需功率 kW	电 动 机		地脚螺栓 GB799-76 (4 个)	螺 母 GB6170-86 (4 个)	垫 圈 GB96-85 (4 个)
									型 号	功率 kW			
3.6	A	1450	1	1332	393	74.2	0.20	0.29	Y90S-4 (B35)	1.1	M8×220	M8	8
			2	1522	381	77.8	0.21	0.31					
			3	1703	369	80.3	0.22	0.33					
			4	1893	353	82.1	0.23	0.34					
			5	2073	335	82.6	0.23	0.35					
			6	2263	313	81.8	0.24	0.36					
			7	2444	285	79.5	0.24	0.36					
			8	2634	247	74.3	0.24	0.36					
4	A	2900	1	4012	2014	77	2.89	3.47	Y132S1-2 (B35)	5.5	M10×220	M10	10
			2	4506	1969	80.3	3.05	3.66					
			3	4973	1915	82.5	3.18	3.82					
			4	5468	1830	84.1	3.28	3.94					
			5	5962	1723	84.6	3.35	4.02					
			6	6457	1606	83.7	3.42	4.11					
			7	6924	1459	81.4	3.43	4.11					
			8	7419	1320	77.5	3.49	4.19					
		1450	1	2006	501	77	0.36	0.54	Y90S-4 (B35)	1.1	M8×220	M8	8
			2	2253	490	80.3	0.38	0.57					
			3	2487	476	82.5	0.40	0.60					
			4	2734	455	84.1	0.41	0.62					
			5	2981	429	84.6	0.42	0.63					
			6	3228	400	83.7	0.43	0.64					
			7	3462	363	81.4	0.43	0.64					
			8	3709	329	77.5	0.44	0.66					
4.5	A	2900	1	5712	2554	77	5.21	6.00	Y132S2-2 (B35)	7.5	M10×220	M10	10
			2	6416	2497	80.3	5.49	6.32					
			3	7081	2428	82.5	5.74	6.60					
			4	7785	2320	84.1	5.92	6.81					
			5	8489	2184	84.6	6.04	6.95					
			6	9194	2036	83.7	6.17	7.09					
			7	9859	1849	81.4	6.17	7.10					
			8	10562	1673	77.5	6.30	7.24					

4-72 № 4. 5A、5A、6A 离心通风机性能与选用件表

机号	传动方式	转速 r/min	序号	流量 m³/h	全压 Pa	内效率 %	内功率 kW	所需功率 kW	电 动 机		地脚螺栓 GB799-76 (4 个)	螺 母 GB6170-86 (4 个)	垫 圈 GB96-85 (4 个)
									型 号	功率 kW			
4.5	A	1450	1	2856	634	77	0.65	0.91	Y90S-4 (B35)	1.1	M8×220	M8	8
			2	3208	620	80.3	0.69	0.96					
			3	3540	603	82.5	0.72	1.00					
			4	3893	577	84.1	0.74	1.04					
			5	4245	543	84.6	0.76	1.06					
			6	4597	506	83.7	0.77	1.08					
			7	4929	460	81.4	0.77	1.08					
			8	5281	416	77.5	0.79	1.10					
5	A	2900	1	7728	3187	77.6	8.72	10.02	Y160M2-2 (B35)	15	M12×300	M12	12
			2	8855	3145	81.8	9.35	10.76					
			3	9928	3074	84.7	9.90	11.39					
			4	11054	2962	86	10.47	12.04					
			5	12128	2792	86.1	10.82	12.44					
			6	13255	2567	84.6	11.07	12.72					
			7	14328	2335	82.1	11.22	12.90					
			8	15455	2019	77.6	11.09	12.75					
		1450	1	3864	790	77.6	1.09	1.42	Y100L1-4 (B35)	2.2	M10×220	M10	10
			2	4427	780	81.8	1.17	1.52					
			3	4964	762	84.7	1.24	1.61					
			4	5527	735	86	1.31	1.70					
			5	6064	693	86.1	1.35	1.76					
			6	6628	637	84.6	1.38	1.80					
			7	7164	580	82.1	1.40	1.82					
			8	7728	502	77.6	1.39	1.80					
6	A	1450	1	6677	1139	77.6	2.71	3.25	Y112M-4 (B35)	4	M10×220	M10	10
			2	7650	1124	81.8	2.91	3.49					
			3	8578	1099	84.7	3.08	3.70					
			4	9551	1059	86	3.26	3.91					
			5	10478	999	86.1	3.36	4.04					
			6	11452	919	84.6	3.44	4.13					
			7	12379	836	82.1	3.49	4.19					
			8	13353	724	77.6	3.45	4.14					

4-72 № 6A、6D、8D 离心通风机性能与选用件表

机号	传动方式	转 速 r/min	序 号	流 量 m³/h	全 压 Pa	内效率 %	内功率 kW	所需功率 kW	电 动 机		地脚螺栓 GB799-76 (4个)	螺 母 GB6170-86 (4个)	垫 圈 GB96-85 (4个)
									型 号	功率 kW			
6	A	960	1	4420	498	77.6	0.79	1.10	Y100L-6 (B35)	1.5	M10×220	M10	10
			2	5065	492	81.8	0.84	1.18					
			3	5679	481	84.7	0.89	1.25					
			4	6324	463	86	0.94	1.32					
			5	6938	437	86.1	0.98	1.37					
			6	7582	402	84.6	1.00	1.40					
			7	8196	366	82.1	1.01	1.32					
			8	8841	317	77.6	1.00	1.30					

机号	传动方式	转 速 r/min	序 号	流 量 m³/h	全 压 Pa	内效率 %	内功率 kW	所需功率 kW	电 动 机		联轴器(套) GB4323-84 (STO103)	地脚螺栓 GB799-76 (4个)	螺 母 GB6170-86 (4个)	垫 圈 GB96-85 (4个)
									型号	功率 kW				
6	D	1450	1	6677	1139	77.6	2.71	3.32	Y112M-4	4	TL6 28×62 48×112 (145-48×28)	M10×220	M10	10
			2	7650	1124	81.8	2.91	3.56						
			3	8578	1099	84.7	3.08	3.77						
			4	9551	1059	86	3.26	3.99						
			5	10478	999	86.1	3.36	4.12						
			6	11452	919	84.6	3.44	4.21						
			7	12379	836	82.1	3.49	4.27						
			8	13353	724	77.6	3.45	4.22						
	960		1	4420	498	77.6	0.79	1.12	Y100L-6	1.5	TL6 28×62 48×112 (145-48×28)	M10×220	M10	10
			2	5065	492	81.8	0.84	1.21						
			3	5679	481	84.7	0.89	1.28						
			4	6324	463	86	0.94	1.35						
			5	6938	437	86.1	0.98	1.39						
			6	7582	402	84.6	1.00	1.32						
		7	8196	356	82.1	1.01	1.34							
		8	8841	317	77.6	1.00	1.33							
8	D	1450	1	15826	2032	77.6	11.42	13.41	Y180L-4	18.5	TL8 48×112 65×142 (200-65×48)	M12×300	M12	12
			2	18134	2065	81.8	12.26	14.39						
			3	20332	1960	84.7	12.98	15.23						
			4	22648	1888	86	13.72	16.1						
			5	24838	1781	86.1	14.18	16.64						
			6	27146	1638	84.6	14.50	17.02						
			7	29344	1490	82.1	14.71	17.26						

4-72 N₂ 8D、10D 离心通风机性能与选用件表

机号	传动方式	转速 r/min	序 号	流量 m³/h	全压 Pa	内效率 %	内功率 kW	所需功率 kW	电动机		联轴器(1套) GB4323-84 (ST0103)	地脚螺栓 GB799-76 (4个)	螺母 GB6170-86 (4个)	垫圈 GB96-85 (4个)
									型号	功率 kW				
8	D	960	1	10478	887	77.6	3.32	4.06	Y132M2-6	5.5	TL8 $\frac{38 \times 82}{65 \times 142}$ (200-65×38)	M10×220	M10	10
			2	12006	875	81.8	3.56	4.36						
			3	13461	856	84.7	3.77	4.61						
			4	14989	825	86	3.98	4.88						
			5	16444	778	86.1	4.11	5.04						
			6	17972	715	84.6	4.21	5.15						
			7	19428	651	82.1	4.27	5.23						
		730	1	7968	512	77.6	1.46	1.93	Y132M-8	3	TL8 $\frac{38 \times 82}{65 \times 142}$ (200-65×38)	M10×220	M10	10
			2	9130	506	81.8	1.56	2.08						
			3	10236	494	84.7	1.66	2.20						
			4	11398	476	86	1.75	2.32						
			5	12504	449	86.1	1.81	2.4						
			6	13666	413	84.6	1.85	2.45						
			7	14773	376	82.1	1.88	2.49						
10	D	1450	1	40441	3202	86.7	41.00	48.12	Y250M-4	55	TL8 $\frac{65 \times 142}{65 \times 142}$ (200-65×65)	M20×500	M20	20
			2	44026	3159	88.7	43.07	50.53						
			3	47611	3032	89	44.59	52.33						
			4	50680	2884	88.2	45.58	53.49						
			5	53664	2722	86.6	46.40	54.45						
			6	56605	2532	84.2	46.86	54.98						
		960	1	26775	1395	86.7	11.9	13.96	Y200L1-6	18.5	TL8 $\frac{55 \times 112}{65 \times 142}$ (200-65×55)	M16×400	M16	16
			2	29148	1376	88.7	12.50	14.67						
			3	31521	1321	89	12.94	15.18						
			4	33554	1257	88.2	13.23	15.52						
			5	35529	1187	86.6	13.47	15.80						
			6	37476	1104	84.2	13.60	15.96						

转速 r/min	序号	流量 m³/h	全压 Pa	内效率 %	内功率 kW	所需功率 kW	电动机		三角带		主轴皮带轮 代号	电机皮带轮 代号	电机导轨部 代号 (2套)	
							型号	功率 kW	型号	根数				内周长 (mm)
1120	1	5157	679	77.6	1.25	1.71	Y100L1-4	2.2	A	2	2240	48-A2-240	28-A2-190	3912-013
	2	5909	670	81.8	1.34	1.83								
	3	6626	655	84.7	1.42	1.94								
	4	7378	631	86	1.50	2.05								
	5	8094	595	86.1	1.55	2.12								
	6	8846	547	84.6	1.59	2.17								
	7	9562	498	82.1	1.61	2.20								
	8	10314	431	77.6	1.59	2.17								
1000	1	4605	541	77.6	0.89	1.31	Y100L1-4	2.2	A	2	2240	48-A2-240	28-A2-170	3912-013
	2	5276	534	81.8	0.95	1.31								
	3	5916	522	84.7	1.01	1.38								
	4	6587	503	86	1.07	1.46								
	5	7227	474	86.1	1.10	1.51								
	6	7898	436	84.6	1.13	1.54								
	7	8538	397	82.1	1.14	1.57								
	8	9209	344	77.6	1.13	1.55								
900	1	4144	438	77.6	0.65	0.96	Y90L-4	1.5	A	2	2240	48-A2-240	28-A2-155	3912-013
	2	4749	432	81.8	0.70	1.03								
	3	5324	422	84.7	0.74	1.09								
	4	5928	407	86	0.78	1.15								
	5	6504	384	86.1	0.80	1.19								
	6	7108	353	84.6	0.82	1.21								
	7	7684	322	82.1	0.83	1.23								
	8	8288	278	77.6	0.82	1.22								
800	1	3684	346	77.6	0.46	0.72	Y80S-4	1.1	A	2	2240	48-A2-240	24-A2-140	3912-013
	2	4221	341	81.8	0.49	0.72								
	3	4733	334	84.7	0.52	0.76								
	4	5270	322	86	0.55	0.81								
	5	5781	303	86.1	0.57	0.83								
	6	6319	279	84.6	0.58	0.85								
	7	6830	254	82.1	0.59	0.86								
	8	7367	220	77.6	0.58	0.85								

转 速 r/min	序 号	流 量 m ³ /h	全 压 Pa	内效率 %	内功率 kW	所 需 功 率 kW	电 动 机		三 角 带		主 轴 皮 带 轮	电 机 皮 带 轮	电 机 导 轨 部	
							型 号	功 率 kW	型 号	根 数				内 周 长 (mm)
1800	1	19646	3143	77.6	21.85	26.45	Y200L1-2	30	B	6	2800	65-B6-320	55-B6-200	3912-015
	2	22511	3101	81.8	23.46	28.39								
	3	25240	3032	84.7	24.83	30.05								
	4	28105	2920	86	26.25	31.77								
	5	30834	2754	86.1	27.12	32.83	Y200L2-2	37	7	65-B7-320	55-B7-200			
	6	33699	2531	84.6	27.74	33.58								
	7	36427	2302	82.1	28.13	34.05								
1600	1	17463	2478	77.6	15.35	18.58	Y180M-2	22	B	5	2240	48-B5-175	3912-014	
	2	20010	2445	81.8	16.47	19.94								
	3	22435	2390	84.7	17.44	21.10								
	4	24982	2303	86	18.43	22.31								
	5	27408	2171	86.1	19.05	23.06	Y200L1-2	30	65-B5-320	55-B5-175				
	6	29954	1996	84.6	19.49	23.59								
	7	32380	1816	82.1	19.76	23.92								
1250	1	13643	1507	77.6	7.32	8.86	Y160M-4	11	B	3	2800	65-B3-320	42-B3-275	3912-014
	2	15633	1487	81.8	7.86	9.51								
	3	17527	1454	84.7	8.31	10.06								
	4	19517	1401	86	8.79	10.64								
	5	21412	1321	86.1	9.08	11.00								
	6	23402	1215	84.6	9.29	11.25								
	7	25297	1106	82.1	9.42	11.40								
1120	1	12224	1209	77.6	5.26	6.37	Y132M-4	7.5	B	2	2800	65-B2-320	38-B2-250	3912-013
	2	14007	1193	81.8	5.65	6.84								
	3	15705	1166	84.7	5.98	7.24								
	4	17487	1124	86	6.32	7.65								
	5	19185	1060	86.1	6.53	7.91	Y160M-4	11	42-B2-250	3912-014				
	6	20968	975	84.6	6.68	8.09								
	7	22666	887	82.1	6.78	8.20								