

(2) Y4-70 II 型锅炉引风机

本机是为适应燃用各种煤质或配有消烟除尘装置的小型(0.5~4t/h)工业锅炉而设计的引风机。最高温度不得超 250℃。性能又相近者均可选用。性能如下

机 号	转 速 r/min	序 号	全 压 Pa	风 量 m³/h	出风口 方 向	电 动 机		传动 方式	外形尺寸 长×宽×高 mm	重量 不含 电机 kg
						型 号	功率 kW			
5	1780	1	726	4410	左右 0° 90° 180°	Y100L-2	3	C	790×900 ×914 (不含电机)	160
		2	755	4940						
		3	755	5460						
		4	736	5990						
		5	706	6520						
		6	687	7040						
		7	657	7570						
		8	618	8100						
	1950	1	863	4830		Y100L-2	3	C	790×900 ×914 (不含电机)	160
		2	903	5410						
		3	903	5990						
		4	883	6560						
		5	844	7140						
		6	834	7720						
		7	795	8300						
		8	736	8870						
	2030	1	942	5030		Y112M-2	4	C		160
		2	981	5630						
		3	981	6230						
		4	952	6830						
		5	922	7440						
		6	903	8040						
		7	863	8640						
		8	804	9240						
	2180	1	1079	5400		Y112M-2	4	C		160
		2	1128	6050						
		3	1099	6690						
		4	1059	7340						
		5	1040	7990						
		6	991	8530						
		7	922	9230						
	2400	1	1305	5940		Y132S1-2	5.5	C		160
2		1364	6650							
3		1364	7360							
4		1334	8070							
5		1285	8780							
6		1256	9490							
7		1197	10200							
8		1118	10910							

Y4-70 II 型锅炉离心引风机性能表

机 号	转 速 r/min	序 号	全 压 Pa	风 量 m³/h	出风口 方 向	电 动 机		传动 方式	外形尺寸 长×宽×高 mm	重量 不含电机 kg
						型 号	功率 kW			
6	1780	1	1040	7630	左右 0° 90° 180°	Y132S1-2	5.5	C	929×1087 ×1083 (不含电机)	170
		2	1079	8540						
		3	1079	9450						
		4	1050	10370						
		5	1020	11280						
		6	991	12190						
		7	952	13100						
		8	893	14010						
	1950	1	1246	8360		Y132S2-2	7.5	C	929×1087 ×1083 (不含电机)	170
		2	1305	9360						
		3	1305	10360						
		4	1265	11360						
		5	1216	12350						
		6	1197	13350						
		7	1138	14350						
		8	1069	15350						
	2030	1	1354	8710		Y160M1-2	11	C		170
		2	1413	9750						
		3	1413	10790						
		4	1373	11830						
		5	1324	12870						
		6	1295	13910						
		7	1236	14950						
		8	1158	15990						
	2180	1	1560	9360		Y160M1-2	11	C		170
		2	1628	10470						
		3	1628	11590						
		4	1579	12700						
		5	1521	13820						
		6	1491	14940						
		7	1422	16050						
		8	1334	17160						
2400	1	1893	10300	Y160M2-2	15	C	929×1087× 1083	170		
	2	1972	11520							
	3	1972	12750							
	4	1913	13970							
	5	1844	15200							
	6	1805	16430							
	7	1717	17660							
	8	1619	18880							